

FASSON®**Product data FASSON MC Primecoat / R100 / BG40 brown**Imprint / **AA0965**

EAN Code : 8712739070170

Spec Code : AA031

Issue date : 17-Feb-2005

FaceStock

A white, one side machine coated, woodfree printing paper with semi-gloss appearance.

Basis Weight	80g/m ²	ISO 536
Caliper	0.069mm	ISO 534

Adhesive

A general purpose removable, rubber based adhesive.

Liner

BG40 brown, a supercalendered glassine paper.

Basis Weight	60g/m ²	ISO 536
Caliper	0.055mm	ISO 534
Transparency	45%	DIN 53147

Laminate

Total Caliper	0.142
---------------	-------

PERFORMANCE DATA

Initial Tack	100N/m	FTM 9 glass
Peel Adhes. 90°	70N/m	FTM 2 st.st.

Min. appl. temp.	-20 °C
Service temp.	-40 °C --> +80 °C

N.B. : All data to be considered as typical values.

Adhesive performance

The adhesive is suitable for general application on a wide range of substrates, featuring good initial tack and adhesion combined with excellent removability. In addition the adhesive has superb low temperature performance.

Remark:

Application to porous substrates such as paper and board, or prolonged exposure to UV light may adversely affect clean removability. The adhesive complies with the European food directives and legislations, FDA 175.105 and the German recommendations XXI as published by BfR. BfR (Bundesinstitut für Risikobewertung) is the German Federal Institute for Risk Assessment. The adhesive can be used in direct contact with dry and moist, non fatty foodstuffs.

Applications and use

Product suitable for promotional labeling applications, labels for supermarkets and general stores as well as for stationary label applications.

Due to the excellent low temperature adhesion performance, this product can also be used successfully in many deepfreeze applications. Typical application areas: General stores, supermarkets, process labeling, industrial labeling.

Conversion / Printing

Good conversion in rotary and flat bed. Complex shaped labels may limit the conversion speed.

Shelf life

Two years when stored at 22°C / 55% RH.



Avery Dennison Roll Materials Europe
Lammenschansweg 140, P.O. Box 28
NL - 2300 AA Leiden - The Netherlands
Tel +31 71 5794100 - Fax +31 71 5794180
<http://www.europe.fasson.com>

Warranty

All statements, technical information and recommendations about AVERY DENNISON products are based upon tests believed to be reliable but do not constitute a guarantee or warranty. All AVERY DENNISON products are sold with the understanding that PURCHASER has independently determined the suitability of such products for its purposes. AVERY DENNISON products are warranted to be free of defects in material or workmanship for a period of one year from the date of shipment. Any product shown to the satisfaction of AVERY DENNISON within the time provided to be so defective shall be replaced without charge or AVERY DENNISON may issue credit in such amount as it deems reasonable however, in no event shall AVERY DENNISON be responsible for claims beyond the replacement value of the defective product or in any way liable or responsible for consequential or incidental damages.

NO EXPRESS WARRANTIES AND NO IMPLIED WARRANTIES, WHETHER OF MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR USE, OR OTHERWISE, EXCEPT AS SET FORTH ABOVE (WHICH IS MADE EXPRESSLY IN LIEU OF ALL OTHER WARRANTIES) SHALL APPLY TO PRODUCTS SOLD BY AVERY DENNISON. AVERY DENNISON SPECIFICALLY DISCLAIMS AND EXCLUDES ALL OTHER SUCH WARRANTIES. NO WAIVER, ALTERATION, ADDITION OR MODIFICATION OF THE FOREGOING CONDITIONS SHALL BE VALID UNLESS MADE IN WRITING AND SIGNED BY AN EXECUTIVE OFFICER OF AVERY DENNISON.

No salesman, representative, or agent of AVERY DENNISON is authorized to give any guarantee, warranty or make any representation contrary to the above.