

Product data FASSON MC70 S2045N-BG30BR FSC

No Imprint / [APF479](#)
EAN Code : 8712739358933
Spec Code : AM403
Issue date : 1-Feb-2012

FaceStock

A white, one side machine coated, woodfree printing paper with semi-gloss appearance.

Basis Weight	70g/m ²	ISO 536
Caliper	0.063mm	ISO 534

Adhesive

A general purpose permanent, rubber based adhesive.

Liner

BG30 brown FSC, a supercalendered glassine paper.

Basis Weight	50g/m ²	ISO 536
Caliper	0.046mm	ISO 534
Transparency	52%	ISO 534

Laminate

Total Caliper	0.116mm	+/- 10%
---------------	---------	---------

PERFORMANCE DATA

Initial Tack	720N/m	FTM 9 glass
Peel Adhes. 90°	360N/m	FTM 2 st.st.
Min. appl. temp.	0 °C	
Service temp.	-40 °C --> +70 °C	

N.B. : All data to be considered as typical values.

Adhesive performance

The adhesive features excellent tack and adhesion on a wide variety of substrates, including apolar, slightly rough and curved substrates. Particularly good performance at lower temperatures, e.g. labeling of chilled products. The adhesive complies with the European food directives and legislations, FDA 175.105 and the German recommendations XXI as published by BfR. BfR (Bundesinstitut für Risikobewertung) is the German Federal Institute for Risk Assessment. The adhesive can be used in direct contact with dry and moist, non fatty foodstuffs.

Applications and use

The product is suitable for a wide range of promotional and industrial label applications where attractive semi-gloss appearance in multi-colour work is required.

A trial is always needed to verify the product / end use suitability.

Conversion / Printing

Facestock is suitable for single and/or multicolour line or process printing by letterpress, offset, flexo, screen and hot foil stamping.

The thinner liner requires more care taken in the die cutting process to avoid over cutting into the liner. There might be limitations for difficult label shapes and high speed wide width converting.

Shelf life

Two years when stored at 22°C . 50% R.H.



Avery Dennison Roll Materials Europe
Lammenschansweg 140, P.O. Box 28
NL - 2300 AA Leiden - The Netherlands
Tel +31 71 5794100 - Fax +31 71 5794180
<http://www.europe.fasson.com>

Warranty

All statements, technical information and recommendations about AVERY DENNISON products are based upon tests believed to be reliable but do not constitute a guarantee or warranty. All AVERY DENNISON products are sold with the understanding that PURCHASER has independently determined the suitability of such products for its purposes. AVERY DENNISON products are warranted to be free of defects in material or workmanship for a period of one year from the date of shipment. Any product shown to the satisfaction of AVERY DENNISON within the time provided to be so defective shall be replaced without charge or AVERY DENNISON may issue credit in such amount as it deems reasonable however, in no event shall AVERY DENNISON be responsible for claims beyond the replacement value of the defective product or in any way liable or responsible for consequential or incidental damages.

NO EXPRESS WARRANTIES AND NO IMPLIED WARRANTIES, WHETHER OF MERCHANTABILITY OR FITNESS FOR ANY PARTICULAR USE, OR OTHERWISE, EXCEPT AS SET FORTH ABOVE (WHICH IS MADE EXPRESSLY IN LIEU OF ALL OTHER WARRANTIES) SHALL APPLY TO PRODUCTS SOLD BY AVERY DENNISON. AVERY DENNISON SPECIFICALLY DISCLAIMS AND EXCLUDES ALL OTHER SUCH WARRANTIES. NO WAIVER, ALTERATION, ADDITION OR MODIFICATION OF THE FOREGOING CONDITIONS SHALL BE VALID UNLESS MADE IN WRITING AND SIGNED BY AN EXECUTIVE OFFICER OF AVERY DENNISON.

No salesman, representative, or agent of AVERY DENNISON is authorized to give any guarantee, warranty or make any representation contrary to the above.